

On the origin of burstiness in human behavior:

The wikipedia edits case

Yerali Gandica<sup>1</sup>, Joao Carvalho<sup>2</sup>, Fernando Sampaio Dos Aidos<sup>2</sup>,

Renaud Lambiotte<sup>1</sup>, and Timoteo Carletti<sup>1</sup>

<sup>1</sup>Department of Mathematics and Namur Center for Complex  
Systems - naXys, University of Namur, rempart de la Vierge 8, B

5000 Namur, Belgium

<sup>2</sup>CFisUC, Department of Physics, University of Coimbra, 3004-516

Coimbra, Portugal

January 11, 2016

**Abstract**

A number of human activities exhibit a bursty pattern, namely periods of very high activity that are followed by rest periods. Records of this process generate time series of events whose inter-event times follow a probability distribution that displays a fat tail. The grounds for such phenomenon are not yet clearly understood. In the present work we use the freely available Wikipedia's editing records to tackle this question by measuring the level of burstiness, as well as the memory effect of the editing tasks performed by different editors in different pages. Our main finding is that, even though the editing activity is conditioned by the circadian 24 hour cycle, the conditional probability of an activity of a given duration at a given time of the day is independent from the latter. This suggests that the human activity seems to be related to the high "cost" of starting an action as opposed to the much lower "cost" of continuing that action.

# 1 Introduction

The digital media is an important component of our lives. Nowadays, digital records of human activity of different sorts are systematically stored and made accessible for academic research. Hence a huge amount of data became available on the past couple of decades, which allows for a quantitative study of human behaviour. For a long time, scholars from different backgrounds have been studying this field: a more general approach by sociologists, and some specific studies by economists and social psychologists. However, some very interesting - and elemental - properties have remained outside the grasp of the research studies for lack of reliable massive stored data. The increasing amount of data that is being gathered in this digital age is progressively opening up new possibilities for quantitative studies of these features. One such aspect, detected by means of data-gathering, is human bursty behaviour, that is the mankind activity characterised by intervals of rapidly occurring events separated by long periods of inactivity [1]. The dynamics of a wide range of systems in nature displays such a behaviour [2].

Given the highly non-linear nature of human actions, their study could hence benefit from the insights provided by the field of complex systems. For the human being, the bursty behaviour phenomenon has been found to modulate several activities, such as sending letters, writing email messages, sending mobile SMS, making phone calls and web browsing [3, 4, 5, 7, 8]. The first works in this field suggested a decision-based queuing process, according to which the next task to be executed is to be chosen from a queue with a hierarchy of importance, in order to explain this behaviour. Different kinds of hierarchies were tested, such as taking into account the task length and deadline constraints [1, 3, 4]. Later on, Malmgren *et al.* [6, 7] argued that decision making is not a necessary component of the bursty human activity patterns. Instead, they maintained that this feature is caused by cyclic constraints in life and they proposed a mechanism based on the coupling of a cascading activity to cyclic repetition in order to explain it. Nonetheless, recently, Hang-Hyun Jo *et al.* [8] applied a de-seasoning method to remove the circadian cycle and weekly patterns from the time series, and obtained similar inter-event distributions, before and after this filtering procedure. In this way, the authors concluded that cyclic activity is also not a necessary ingredient of bursty behaviour. However they do not provide an explanation for the fundamental origin of burstiness. Such explanation is still missing in the literature and the scope of this article is to add some new insights into this issue by looking into Wikipedia editing.

The success of research in digital social patterns hinges on the access to high quality data. Even though the availability of recorded data and its accessibility are rapidly increasing, many data sets are not freely available for research. Wikipedia (WP) is an important exception, as not only is it considered a robust and trustworthy source of information [9], but it is also easily accessible via the API [10] or the different available dumps [11]. The accessible data contain the whole editing history record for both pages and editors. We start by showing that this database captures the bursty nature of the human actions, and that the human activity region described by the bursty coefficient and memory effect in [4] must be increased if it is to accommodate the editing activity of Wikipedia. We also show the cyclic nature of the data and the circadian patterns in WP editing. Most interestingly, we show how, although the editing

activity is strongly constrained by the time of day at which it happens, the final probability distribution of the inter-event times is quite independent of that, displaying a fat tail that is robust against changes of editing time during the day. This suggests that burstiness in human behaviour is mostly independent of cycles in life. Finally, we look into the effect that stationarity may have on burstiness; whether a change on editing activity over time may be the cause for the fat tail of the inter-event distribution. Our results indicate that burstiness is common to all editors, whether their editing history is stationary or not, which suggests that there does not seem to be a cause and effect relationship between non-stationarity and burstiness. Having discarded cycles in life and non-stationarity as possible causes for burstiness, our findings suggest a sort of robust distribution for the time between activities, set internally by individuals.

## 2 Methods

Our data sample is a database of Wikipedia (WP) edits of all the pages written in English in the period of 10 years ending on January 2010; the dump contains  $4.64 \times 10^6$  pages [12]. For each entry, we know: the Wikipedia page name, the edit time stamp and the identification of the editor who did the changes. We analyse the information separately for each page and for each editor and, in order to reduce the impact of outliers, we did not consider the pages or editors with less than 2000 activities. This number is a good compromise between having enough pages/editors and the pages being frequently updated or the editor being reasonably active in this time span. We also remove from the data the edits made by WP-bots, which are programs that go through the WP carrying out automatically repetitive and mundane tasks to maintain the WP pages (as software programs, their edit pattern is different from the humans'). A list of the bots can be found in [13]. Moreover, we discard entries associated to IP's and only consider editors who login before editing, so that the editor is univocally identified.

In order to obtain the power spectrum of the editing activity shown in Fig. 3 for editors and in Fig. 4 for pages, we binarized our activity record for any editor and any page with small enough bins to contain at most one edit. Finally we performed a fast Fourier transform (FFT) on such preprocessed data. Although in every 5,000 edits there is one second with more than one edit, we checked that the results do not change if these values are truncated to one (for the editors this must correspond to a double saving operation in the same second and this should reasonably be counted as one).

## 3 Results

### 3.1 Bursty level and Memory effects

Let  $E_i$  be a variable that identifies each editor in our sample,  $t_n^{E_i}$  the time at which  $E_i$  edits for the  $n$ th time and  $\tau_n^{E_i} = t_{n+1}^{E_i} - t_n^{E_i}$  the  $n$ th inter-event time for that editor (where obviously  $n \geq 1$ ). For the sake of clarity in the equations, we avoid this cumbersome notation and omit the superscript  $E_i$ , writing just  $t_n$  and  $\tau_n$  for short. These should be understood as referring the specific editor that is

being considered. The same will apply to the other variables in the following equations.

A standard measure of burstiness has been provided by Goh *et al.* [4]. For editor  $E_i$  we obtain:

$$B_i \equiv \frac{\sigma - m}{\sigma + m}, \quad (1)$$

where  $m$  and  $\sigma$  are, respectively, the mean and standard deviation of the set of values  $\tau_n$  which refer to editor  $E_i$ . Parameter  $B_i$  measures the magnitude of the variance in comparison to the mean, and goes from -1 ( $\sigma \ll m$ ), for periodic signals, to 1 ( $\sigma \gg m$ ) for strongly bursty distributions.

In order to have a better characterisation for the general behaviour of the editing process, we also compute the memory coefficient  $M_i$ , for editor  $E_i$ , which is also defined in [4]:

$$M_i \equiv \frac{1}{n_\tau - 1} \sum_{j=1}^{n_\tau-1} \frac{(\tau_j - m_\tau)(\tau_{j+1} - m'_\tau)}{\sigma_\tau \sigma'_\tau}, \quad (2)$$

where  $n_\tau$  is the number of inter-event values for that particular editor (equal to the number of edits minus 1), and  $m_\tau$  and  $\sigma_\tau$  ( $m'_\tau$  and  $\sigma'_\tau$ ) are, respectively, the average and the standard deviation of the set of all inter-event times except the last one (the first one). This coefficient is very similar to the autocorrelation function for consecutive inter-events and is positive when short (large) inter-event times tend to be followed by short (large) inter-event times, negative in the opposite case and otherwise close to zero.

In Fig. 1 we show the scatter plot of the joint distributions of  $M_i$  and  $B_i$ . We can see that the main population has high values of burstiness and, at the same time, low memory effects, meaning that there is small correlation between the sizes of the time span of two consecutive inter-events. The average values obtained for  $B_i$  and  $M_i$  are  $\langle B \rangle = 0.770$  and  $\langle M \rangle = 0.125$ , values that result to be outside the region of human behaviour reported by Goh *et al.* [4] (red zone in figure 4 of [4]).

The value for  $\langle M \rangle$  is small but it is statistically different from zero, as we now show. The normalised distribution of the values of  $M_i$  for all the editors is shown in the left panel of Fig. 2. The distribution is very skewed, with very few negative values. To determine whether the average value obtained for  $M_i$  is statistically relevant (different from zero) we built a null-model. For each editor, we reshuffled the sequence of inter-event times  $\tau_i$  and obtained a new sequence  $\theta_i$  where all possible time correlations have been destroyed. Then, we computed the memory coefficient  $\tilde{M}_i$  of such new sequence. Finally we repeated such a process 100 times and computed the average  $\overline{M}_i$  of all the memory coefficients, as well as its standard deviation  $\overline{\sigma}_i$ .

The normalised distribution of  $\overline{M}_i$  is shown in the middle panel of Fig 2. We can see that  $\overline{M}_i$  is basically zero, due to the elimination of the memory (time correlations) by the reshuffling. On the right panel of the same figure we report the normalised distribution of the z-scores  $z_i = \frac{M_i - \overline{M}_i}{\overline{\sigma}_i}$ . From the latter plot we confirm that the average of  $\langle M \rangle - \overline{M}_i$  (which is basically equal to  $\langle M \rangle$ ) is large enough, in terms of standard deviations, to conclude that the value of  $\langle M \rangle$  is statistically relevant and different from zero.




Figure 1: Scatter plot for the joint distribution of Burstiness,  $B_i$ , versus Memory coefficient,  $M_i$ .

### 3.2 The cyclic nature of WP editing

WP editors, as much as anybody else, live in a dynamic environment, strongly conditioned by periodic factors: day/night, weekdays/weekends, seasons, etc. It is thus important to check whether their WP activity is also conditioned by such regularities. For this purpose, we selected the 100 most active editors and computed the Fourier power spectrum of each editor time activity, as explained in the methods. The results for two representative editors are reported in Fig. 3 where we show the power spectrum for editors  $E_1$  (left) and  $E_2$  (right). In each panel a main peak is clearly visible at  $\sim 1.157 \times 10^{-5}$  Hz corresponding to a period of 24 hours as well as a second peak at  $\sim 2.315 \times 10^{-5}$  Hz associated to a 12 hours period (a harmonic of the main peak). Other harmonics are also visible, especially in the right panel. We checked that these values are robust against the choice of the bin size, from a few seconds up to several hours, used to perform the FFT.

In order to check whether this periodicity is particular to human behaviour, we repeated this procedure for the WP pages. We selected the 100 pages with more edits and evaluated the Fourier power spectrum in the same way that was done for the editors. We found that, in general, pages lack predominant peaks in the power spectrum. They appear only in pages related to records (for example births/deaths counting) or companies, which in general update their pages daily. In figure 4, we show the power spectrum of a generic page in the left panel, as an example for the general behaviour found in the WP pages. In the right panel we show the power spectrum of the WP page of a big company. In the latter case, we can see clearly the one day period that is lacking in the generic WP page. It is interesting that pages do not show periodic behaviour, even though they are edited by editors who do show that behaviour. The conjugation of many different editors, with different editing rhythms, wipes out the periodicity, just like summing many oscillators with random phases.




Figure 2: The memory coefficient. Left panel: Distribution of  $M_i$  for all the editors with more than 2000 edits. Middle panel: Distribution of the averages  $\overline{M}_i$  for the null-model computed using 100 replicas for each editor. Right panel: Distribution of the z-score values.

A better illustration of these circadian patterns can be found in Fig. 5, which shows the average number of edits over a period of one week (left) and one day (right) of editors  $E_1$  (top) and  $E_2$  (bottom), as a function of the editing time. To build the daily (weekly) plot, we divided the whole time span of our data of about ten years into days (weeks), and then divided each day (week) in 48 (168) windows with 30 (60) minutes each. For each window, we computed the average number of edits that were performed inside that window for every day (week) for the whole 10 year time span. That gives the daily (weekly) average activity which is plotted in Fig. 5.

The circadian patterns are visible in the plots; each editor exhibits clearly one peak (sometimes two peaks) of activity every day. We can also see a daily trough of low activity that will probably correspond to the time when the editor rests.

### 3.3 Robustness of the inter-event distribution

In the previous section we have shown that editing is strongly influenced by the circadian cycle; in this section we analyse whether these circadian patterns have consequences on the inter-event probability distribution. To perform such an analysis we computed the probability distribution for inter-events of a given duration assuming that they have been saved at a particular time of day. If this probability depends on the time of day at which they are recorded, then the time spent in a human activity is also dictated by cycles and thus the origin of burstiness can possibly be ascribed to this phenomenon; on the other hand, if




Figure 3: Fourier spectrum of the editing activity for editors  $E_1$  and  $E_2$ . One can clearly identify the main peak  $f_1 \sim 1.157 \times 10^{-5}$  Hz corresponding to a 24 hours period and, especially on the right panel, several harmonics.




Figure 4: Power spectrum of two different types of Wikipedia pages. The left panel corresponds to a generic issue and the right panel to a big company. Note the one day periodicity in the latter and the absence of peaks in the former.

the probability to perform an activity that lasts a definite amount of time does not depend on the time of day at which it is registered, then we can conclude that burstiness in WP editing does not depend on the periodically changing environment.

Results reported in Fig. 6 support the latter hypothesis. The inter-event probability distributions computed in different time windows, with a one hour time span, exhibit a similar fat tail when they are normalized by the number of event in that hour. Note that only 17 time windows are shown in Fig. 6. Seven windows were left out as they correspond to the periods of low activity shown in Fig. 5 and had too little data to be relevant.

This seems to indicate that, although the event probability responds to strong circadian patterns during the day, the bursty nature of the process is not a consequence of that cyclic behaviour. In ref [8], the authors reported the independence of burstiness with respect to the 24 hour cycles, showing the




Figure 5: The left panels show the editing activity as a function of the week day, averaged over the data time span (about ten years) for two of the most active editors,  $E_1$  (top) and  $E_2$  (bottom). Circadian patterns are clearly visible. In general, we can identify a different editing activity over the week-ends (dark area). The right panel shows the average editing distribution along the day. One main peak of activity is clearly visible, as well as a time span of very low activity (presumably corresponding to a resting period).

same inter-event distribution in windows of one day. What we show here is the same inter-event distribution but in windows of one hour, where the brevity of the time windows provides a good proxy for the independence of the activity duration from the time of day of its realisation. This kind of universality has been reported in phenomena emerging from the joint action of several individuals [22, 23]. However, to the best of our knowledge, the occurrence of this phenomenon as a result of a single person’s decision has not been reported previously in the literature.

Finally we must discard any effects on the bursty nature of the data due to changes in the editing activity along the years [7]. We check the stationarity of the time series of editors by splitting it into ten windows, each one corresponding to the same time span, and comparing the probability distributions of inter-events of all ten windows with each other. We have done that for the editing data of several editors.

In order to compare the ten probability distributions with one another, we used the Kolmogorov-Smirnov (KS) test. Some editors show, indeed, a lack of






Figure 6: Probability distributions for the inter-event times of editors  $E_1$  and  $E_2$  for different values of the inter-event time. Each color-symbol represents the probability distribution for the inter-event times that are recorded during each of the 17 one hour windows of the day. Seven windows were left out because the small quantity of data they contain was not sufficient to draw statistically sounding conclusions. One can clearly appreciate the similar fat-tail distributions of inter-events, independently of the circadian patterns of data. Observe also that the inter-event duration is limited to a few hours; this is due to our choice to present data for editors who have a very high activity and consequently relatively short inter-event durations. In both panels, the dotted lines represent the best fit.

stationary behavior on the time scale of one year. However, there are some for which the probability distributions are very similar across the ten windows. As an example, we show in Fig. 7 the results for four editors. For each editor, we show in the left panel the distribution of the inter-event times for each of the ten windows, while in the right panel we show the results of the Kolmogorov-Smirnov test for all combinations of different time windows. Both panels seem to indicate that the distributions shown on the left-hand side are stationary, while the distributions shown on the right-hand side become somewhat stationary after the fourth time window onwards. In the top row we show the results for editors  $E_1$  and  $E_2$  mentioned before, who have different degrees of behaviour towards stationarity. Nevertheless, our previous results stand for both of them, thus suggesting that the somewhat lack of stationarity of editor  $E_2$  does not affect our previous results.

In table 1 we show the values of  $B$  for each of the ten time windows, as well as the values for the whole data span. We can see that  $B$  is high in each window, which seems to confirm the lack of correlation between burstiness and non-stationarity.




Figure 7: Study of stationarity for ten time windows, covering the whole editing time span for editors  $E_1$  (top left),  $E_2$  (top right),  $E_3$  (bottom left) and  $E_4$  (bottom right). For each editor, in the left panel we show the inter-event distributions and in the right panel the results of the Kolmogorov-Smirnov test (comparison for all possible combinations of time intervals).

## 4 Discussion

In this work, we study bursty behavior in human activities and try to understand its origin. Using data from Wikipedia editing, we have measured the average level of burstiness  $B$  and memory  $M$  of editors, using standard indicators. Remarkably, our results fall outside the region in the  $(M, B)$  plane ascribed to human activity as proposed by [4], thus suggesting that such region should be enlarged.

We showed that the events are strongly conditioned by the circadian cycle of 24 hours, while the inter-events are stationary on the same time scale. This suggests that burstiness is not a consequence of the cyclic nature of human activity. Instead, it seems to be intrinsic to mankind nature: before performing an action

Table 1: Values of burstiness for all data and in time windows, for editors  $E_1$ ,  $E_2$ ,  $E_3$  and  $E_4$ .

Data	$B(E_1)$	Length	$B(E_2)$	Length	$B(E_3)$	Length	$B(E_4)$	Length
all data	0.617	106824	0.912	267006	0.776	156876	0.850	130408
window 1	0.638	9374	0.844	9955	0.846	11348	0.888	12529
window 2	0.738	12023	0.800	15391	0.784	17427	0.829	9600
window 3	0.632	11443	0.857	30343	0.702	10694	0.864	11967
window 4	0.577	12912	0.898	26440	0.716	10492	0.785	12533
window 5	0.549	10223	0.877	33079	0.755	16288	0.868	13641
window 6	0.566	11316	0.896	21478	0.727	11687	0.806	10457
window 7	0.568	11907	0.905	37167	0.736	19474	0.809	15273
window 8	0.576	7170	0.890	24836	0.781	18496	0.840	21058
window 9	0.574	10376	0.904	41526	0.759	19542	0.860	10839
window 10	0.578	10080	0.958	26791	0.737	21428	0.829	12511

(make a phone call, write an email, edit Wikipedia, etc) we must overcome a “barrier”, acting as a cost, which depends, among many other things, on the time of day. However, once that “barrier” has been crossed, the time taken by that activity no longer depends on the time of day at which we decided to perform it. Instead, there is a robust distribution of dedicated time in proportion to the different amount of activities that the individual is able to do at specific times. It could be related to some sort of queuing process, but we prefer to see it as due to resource allocation (attention, time, energy), which exhibits a broad distribution: shorter activities are more likely to be executed next than the longer ones, which ultimately may be responsible for the bursty nature of human behavior. We verified that our results are independent of the effect of non-stationarity.

### Acknowledgments

The work of Y.G., T.C. and R. L. presents research results of the Belgian Network DYSCO (Dynamical Systems, Control, and Optimisation), funded by the Interuniversity Attraction Poles Programme, initiated by the Belgian State, Science Policy Office.

## References

- [1] Barabási A-L 2005 The origin of bursts and heavy tails in human dynamics *Nature* **435** 207-11.
- [2] Hidalgo C 2006 Conditions for the emergence of scaling in the inter-event time of uncorrelated and seasonal systems *Physica A* **369** 877-83.
- [3] Vázquez A, Gama Oliveira J, Dezső Z, Goh K-I, Kondor Barabási A-L 2006 Modeling bursts and heavy tails in human dynamics *Phys. Rev. E* **73**, 036127.
- [4] Goh K-I. and Barabási A-L 2008 Burstiness and memory in complex systems *EPL* **81** 48002.
- [5] Wu Y et al., 2010 Evidence for a bimodal distribution in human communication *PNAS* **107** 18803.
- [6] Malmgren RD. et al. 2008 Poissonian explanation for heavy tails in e-mail communication *PNAS* **105** no. 47, 18153.
- [7] Malmgren RD. et. al., 2009 On Universality in Human Correspondence Activity *Science* **325** 1696.
- [8] Hang-Hyun J et al., 2012 Circadian pattern and burstiness in mobile phone communication *New Journal of Physics* **14** 013055.
- [9] Giles J 2005 Internet encyclopaedias go head to head *Nature* **438** 900.
- [10] [https://www.mediawiki.org/wiki/API:Main\\_page](https://www.mediawiki.org/wiki/API:Main_page)

- [11] [https://en.wikipedia.org/wiki/Wikipedia:Database\\_download](https://en.wikipedia.org/wiki/Wikipedia:Database_download)
- [12] <http://wmm.phy.bme.hu/>.
- [13] [https://en.wikipedia.org/wiki/Category:All\\_Wikipedia\\_bots](https://en.wikipedia.org/wiki/Category:All_Wikipedia_bots)
- [14] Gandica Y, Carvalho J and Sampaio Dos Aidos F 2015 Wikipedia editing dynamics. *Phys. Rev. E* **91** 012824.
- [15] Halfaker A, Kittur A, Kraut R, and Riedl J 2009 A Jury of Your Peers: Quality, Experience and ownership in Wikipedia, in WikiSys09: Proceedings of the 5th International Symposium on Wikis and Open Collaboration, edited by D. Riehle (ACM, New York, 2009), Article no. 15.
- [16] Kimmons RM 2011 Understanding collaboration in Wikipedia. *First Monday* **16** 12.
- [17] Bianconi G and Barabási A-L 2001 Competition and multiscaling in evolving networks *Europhys. Lett.* **54** 436.
- [18] Dorogovtsev SN and Mendes JFF 2001 Scaling properties of scale-free evolving networks: Continuous approach *Phys. Rev. E* **63** 056125.
- [19] Vicent Gómez NL, Hilbert J Kappen, and Kaltenbrunner A 2013 A likelihood-based framework for the analysis of discussion threads *World Wide Web* **16** 645.
- [20] Dorogovtsev SN and Mendes JFF 2000 Evolution of networks with aging of sites *Phys. Rev. E* **62** 1842.
- [21] Javanmardi S, Lopes C, and Baldi P 2010 Modeling User Reputation in Wikis *Statistical Analysis and Data Mining: The ASA Data Science Journal* **3** 126.
- [22] Fortunato S and Castellano C 2007 Scaling and universality in proportional elections *PRL* **99** 138701.
- [23] Radicchi F, Fortunato S and Castellano C 2008 Universality of citation distributions: toward an objective measure of scientific impact *PNAS* **105** 17268.